Home ESS-HV Series



DESCRIPTION



Home energy storage system, modular highvoltage battery, suitable for residential energy storage, one set to solve the electricity consumption of the whole house.

FEATURES



Using safe lithium iron phosphate square battery as the main body of energy storage, with feature of large capacity, light weight, large power;



Modular structure, can form a small combination of various energy levels, easy maintenance, plug and play;



Modular design for fast transportation and easy installation



LED lights display the parameters of the equipment in real time, and the running status is clear at a glance;

- It can match to main hybrid inverter in the market, easy to use
- With functions of over charge and discharge protection, power supply monitoring and low power alarm;
- The maximum capacity of a single cluster is 20.48kWh, and it supports 16 clusters in parallel



TECHNICAL PARAMETER

| Pack Number | 3 | 4 | 5 | 6 | 7 | 8 |
|------------------------|--------------------------------------|---------------|---------|---------------|---------------|---------------|
| Capacity (KWh) | 7. 68 | 10. 24 | 12. 8 | 15. 36 | 17. 92 | 20. 48 |
| Cell Serial parallel | 48S1P | 64S1P | 80S1P | 96S1P | 112S1P | 128S1P |
| Nominal voltage (V) | 136. 8-172. 81 | 182. 4–230. 4 | 228-288 | 273. 6–345. 6 | 319. 2-403. 2 | 364. 8-460. 8 |
| Nominal energy (kWh) | 7. 68 | 10. 24 | 12. 8 | 15. 36 | 17. 92 | 20. 48 |
| Pack Dimension (mm) | 550*380*130 | | | | | |
| Cell Type | LFP (LiFeP04) | | | | | |
| Nominal Current(A) | 50 | | | | | |
| Communication Type | CAN/RS485 | | | | | |
| Working Temperature: | Charge: 0-45°C / Discharge: -20-50°C | | | | | |
| Working Humidity (Rh | 0–95 Rh | | | | | |
| Working Altitude (m) | | | < | ≤4000m | | |
| Morking Artitude (III) | ~4000III | | | | | |
| IP Level | IP65 | | | | | |
| Installation Type | Floor Type | | | | | |
| Life Cycle | 10 Years | | | | | |
| | | | | | | |

APPLICATION





